UNICA

D033X SINGLE COAT LOW VOC WATER-BASED PAINT

DESCRIPTION

UNICA is a low VOC water-based emulsion paint formulated with acrylic polymers, very fine mineral aggregates and colored pigments which are stable to light and weather.

UNICA is a professional product for interior wall surface with excellent technical application characteristics. The applied film is perfectly matt and anti-glare, capable of masking existing wall imperfections and has high mold resistant.

Excellent coverage, easy setting of color and absence of defects for retouching without hot spots or shading.

UNICA is an eco-green paint, formaldehyde free. It is highly washable and has anti-mold and fungicide properties.

UNICA is suitable for interior surfaces of public or private structures which require a high degree of finish and aesthetic appearance. It can be applied on plaster, plasterboard, finished cement, cement board, masonite, concrete, wood, plastic (PVC).

UNICA is supplied in white colour (BIANCO).

SUDEACE DREDADATION

SURFACE PREPARATION		
SURFACE	PREPARATION TIPS	
Lime based mortar	Direct application	
Old plaster	Brushing and pressure washing +	
	1 coat of DOC PRIMER	
Tempera	Brushing + 1 coat of DOC PRIMER	
Breathable paint	Brushing + 1 coat of DOC PRIMER	
MDF	1 coat of DOC PRIMER	
Plasterboard	1 coat of DOC PRIMER	
Gypsumboard	1 coat of DOC PRIMER	
Concrete	1 coat of DOC PRIMER	
Lime based glossy	Sanding + 1 coat of DOC PRIMER	
finish		
Washable paint	1 coat of DOC PRIMER	
Acrylic decorative	1 coat of DOC PRIMER	
paint		
Wood	1 coat of DOC PRIMER	
Plastic (PVC)	Washing + 1 coat of DOC PRIMER	

APPLICATION

UNICA is a ready-to-use water-based paint. It may be diluted with max 5% water.

Mix UNICA well and apply at least one coat of product over primed surface. In case of verv absorbent, uneven or excessively charged surface, a second coat may be necessary.

At the time of application, the substrate must be sufficiently dry. Do not apply on substrate with rising damp or with the presence of efflorescence. In case of low temperature and high humidity, allow longer drying time between coats, otherwise swelling is possible.

The information provided is based on our experience and technical and scientific knowledge; nonetheless, we may not be held liable for the results obtained using these products, as application conditions are beyond our control. It is recommended to always make sure that the product is suited to each specific use.



Poor quality substrate (tempera and degraded stucco) can give rise to bubbles and detachments.

In order to obtain required performances, it is important that the indicated consumption and thickness are respected.

ENVIRONMENTAL CONDITIONS

During application, the environmental temperature has to be between +5°C and +40°C (+40°F and +104°F) while relative humidity has to be less than 85%, even after 24 hours after application.

STORAGE

UNICA maintains its properties in storage for 24 months if protected from excessive heat and cold. Storage temperature must be between +1°C and +45°C. KEEP FROM **FREEZING.** Do not store product diluted with water.

SAFETY GUIDELINES

Avoid contact with skin and eyes. If contact occurs, rinse thoroughly with water. For further information, consult the MSDS.

DISPOSAL

The material has to be disposed in agreement with local regulation. Empty plastic containers are recyclable or to be sent to recycling plants.

UNICA EXTRA TECHNICAL TABLE

A 1	
Aspect	matt
Packaging	4 , 13
Application tools	Brush, roller, spray
Dilution	Max 5% with water
Density	1.46 ± 0.05 Kg/l
Theoretical yield	approx. 10-12m ² /l in one coat
Dry volumetric	55% ± 2
residue	
Touch dry	3-4 hours at 25°C temperature
Dry to handle	18-24 hours at 25°C temperature
Dry to recoat	5-6 hours at 25°C temperature
Wet abrasion	Din 53778, >4500
Wash resistance	ISO 11998, Class 1
Briliance	EN ISO 2813, Very Opaque <5
VOC	<0.01g/l
HS CODE	3209.10.0000

MTDS 033XENG Document Issuing date 01.09.2021



is a brand of Decora A&C Pte Ltd, Designed in Singapore and manufactured entirely in Italy info@decora-art.com

Revision