RUST.IT ATTIVATORE

D043 AMMONIA ACTIVATOR IN SOLUTION

DESCRIPTION

RUST.IT ATTIVATORE is an ammonia solution, used as an activator for the RUST.IT product

APPLICATION

After 4-6 hours (make sure the product is dry) from the last coat of RUST.IT it is possible to proceed with the corten-rust decoration of the surface, using RUST.IT ATTIVATORE:

Apply a first layer using a spalter brush, sponge or spray, after 4-6 hours (depending on the environmental conditions) repeat the operation in order to obtain the desired rust-corten effect, bear in mind that applying more coats of RUST.IT ATTIVATORE accentuates the rust effect.



ENVIRONMENTAL CONDITIONS

During application, the environmental temperature has to be between +10°C and +30°C (+50°F and +95°F) while relative humidity has to be less than 80%, even after 24 hours after application. NOT RECOMMENDED IN PRESENCE OF STRONG **RISING OR PERMANENT HUMIDITY.**

STORAGE

RUST.IT ATTIVATORE maintains its properties in storage for 24 months if protected from excessive heat and cold. Storage temperature must be between +5°C and +35°C. **KEEP FROM FREEZING.**

SAFETY GUIDELINES

Avoid contact with skin and eyes. If contact occurs, rinse thoroughly with water. For further information, consult the MSDS.

DISPOSAL

The material has to be disposed in agreement with local regulation. Empty plastic containers are recyclable or to be sent to recycling plants.

INFINITY TECHNICAL TABLE

Aspect	liquid
Packaging	0.75L
Application tools	Brush, short-haired roller or spray
Specific weight	1.000 ± 0.05 Kg/l
Theoretical yield	7 - 10 m2/lt in two coats according to absorption
Volumetric dry residue	35 ± 2%
Touch dry	4-6 hours no restrictions
Dry to handle	12-18 hours at 20°C temperature
Dry to recoat	12 hours at 20°C temperature
VOC	10g/l wall paint and subcategory L
	max value UE2010: 30g/l
HS CODE	3209.90.00

The information provided is based on our experience and technical and scientific knowledge; nonetheless, we may not be held liable for the results obtained using these products, as application conditions are beyond our control. It is recommended to always make sure that the product is suited to each specific use.

Document

MTDS 042ENG



is a brand of Decora A&C Pte Ltd, Singapore, designed and manufactured entirely in Italy info@decora-ac.com

Revision

Issuing date