

DESCRIPTION

SPACE is a metallic paint with metallic power based on terpolyacrylic resin gels and special additives in aqueous dispersion

Its eco-friendly formulation improves interior living comfort, granting energy saving throughout the year, in keeping with an aesthetic hint and a modern taste.

SPACE grants good water permeability and is supplied in **SILVER** and **GOLD**.

SURFACE PREPARATION

SURFACE	PREPARATION TIPS
New or painted surface	Brushing + 1 coat of DOC PRIMER + 1 coat of UNICA
Uncoherent and irregular substrate	Fix any crack, remove loose and friable parts, clean and brush thoroughly, then apply 1 coat of DOC PRIMER + 1 coat of UNICA
MDF, PVC	Brushing + 1 coat of DOC PRIMER + UNICA
MDF	1 coat of DOC PRIMER + 1 coat of UNICA
Plasterboard	1 coat of DOC PRIMER + 1 coat of UNICA
Gypsumboard	1 coat of DOC PRIMER + 1 coat of UNICA
Concrete	1 coat of DOC PRIMER + 1 coat of UNICA
Lime based glossy finish	Sanding + 1 coat of DOC PRIMER + 1 coat of UNICA
Washable paint	1 coat of DOC PRIMER + 1 coat of UNICA
Acrylic decorative paint	1 coat of DOC PRIMER + 1 coat of UNICA
Plastic rendering	Washing + 1 coat of DOC PRIMER + UNICA

APPLICATION

SPACE is a ready-to-use decorative paint. Mix carefully before use.

FIRST COAT

Consumption: approx. 0.65 - 0.75 kg/m²

Spread **SPACE** on the wall evenly to cover the entire surface, and then use the selected tool to reach the desired effect.

According to the different tool, you can obtain:

Vertical or Horizontal **bamboo effect**, by using the grass pad;

brick effect, by using the steel spatula and alternate it from left to right, and right to left;

leaf effect, with semicircular strokes;

web effect, with the web roller;

croco effect, with the crocodile roller.

ENVIRONMENTAL CONDITIONS

During application, the environmental temperature has to be between +10°C and +30°C (+50°F and +95°F) while relative humidity has to be less than 85%, even after 24 hours after application. **NOT RECOMMENDED IN PRESENCE OF STRONG RISING OR PERMANENT HUMIDITY.**

STORAGE

SPACE maintains its properties in storage for 12 months if protected from excessive heat and cold. Storage temperature must be between +5°C and +35°C. **KEEP FROM FREEZING.**

SAFETY GUIDELINES

Avoid contact with skin and eyes. If contact occurs, rinse thoroughly with water. For further information, consult the MSDS.

DISPOSAL

The material has to be disposed in agreement with local regulation. Empty plastic containers are recyclable or to be sent to recycling plants.

SPACE TECHNICAL TABLE

Aspect	metallic paste
Packaging	1l, 4l
Application tools	stainless steel and roller
Specific weight	1.15 ± 0.05 Kg/l
Theoretical yield	approx. 0.65-0.75kg/m ² (one coat)
Volumetric dry residue	40 ± 2%
Viscosity	thixotropic
Coating thickness	0.40 - 0.50 mm
Touch dry	6-8 hours at 20°C temperature
Dry to handle	18-24 hours at 20°C temperature
Dry to recoat	18 hours at 20°C temperature
VOC	10g/l wall paint and subcategory L max value UE2010: 30g/l
HS CODE	3209.90.00