

## DESCRIPTION

**INFINITY** is a decorative metallic paint based on acrylic resins and special transparent additives in aqueous dispersion. Its pyramidal particles along with the accurate application technique create a highlighted luster and a velvet touch effect, making **INFINITY** suitable with any kind of architectural style, from classic to modern.

**INFINITY** can be applied on any internal surface, such as masonry, MDF, PVC, following the correct preparation.

**INFINITY** is supplied 4 colors, **WHITE, SILVER, GOLD** and **GREY**.

## SURFACE PREPARATION

SURFACE	PREPARATION TIPS
New or painted surface	Brushing + 1 coat of <b>DOC PRIMER</b> + 1 coat of <b>UNICA</b>
Uncoherent and irregular substrate	Fix any crack, remove loose and friable parts, clean and brush thoroughly, then apply 1 coat of <b>DOC PRIMER</b> + 1 coat of <b>UNICA</b>
MDF, PVC	Brushing + 1 coat of <b>DOC PRIMER</b> + <b>UNICA</b>
MDF	1 coat of <b>DOC PRIMER</b> + 1 coat of <b>UNICA</b>
Plasterboard	1 coat of <b>DOC PRIMER</b> + 1 coat of <b>UNICA</b>
Gypsumboard	1 coat of <b>DOC PRIMER</b> + 1 coat of <b>UNICA</b>
Concrete	1 coat of <b>DOC PRIMER</b> + 1 coat of <b>UNICA</b>
Lime based glossy finish	Sanding + 1 coat of <b>DOC PRIMER</b> + 1 coat of <b>UNICA</b>
Washable paint	1 coat of <b>DOC PRIMER</b> + 1 coat of <b>UNICA</b>
Acrylic decorative paint	1 coat of <b>DOC PRIMER</b> + 1 coat of <b>UNICA</b>
Plastic rendering	Washing + 1 coat of <b>DOC PRIMER</b> + <b>UNICA</b>

## APPLICATION

**INFINITY** is a ready-to-use decorative paint. Mix carefully before use.

### FIRST COAT

Consumption: approx. 10-12 m<sup>2</sup>/l  
Spread **INFINITY** on the wall with the stainless-steel trowel evenly to cover the entire surface.

### SECOND COAT

Consumption: approx. 10-12 m<sup>2</sup>/l  
Once the first coat is completely dry (minimum 4 hours), apply a second and final coat of **INFINITY**, proceeding for about 1sqm at a time, covering completely the selected area and floating the stainless-steel trowel flat onto the surface, to create light and shade effects.

## ENVIRONMENTAL CONDITIONS

During application, the environmental temperature has to be between +10°C and +30°C (+50°F and +95°F) while relative humidity has to be less than 85%, even after 24 hours after application. **NOT RECOMMENDED IN PRESENCE OF STRONG RISING OR PERMANENT HUMIDITY.**

## STORAGE

**INFINITY** maintains its properties in storage for 12 months if protected from excessive heat and cold. Storage temperature must be between +5°C and +35°C. **KEEP FROM FREEZING.**

## SAFETY GUIDELINES

Avoid contact with skin and eyes. If contact occurs, rinse thoroughly with water. For further information, consult the MSDS.

## DISPOSAL

The material has to be disposed in agreement with local regulation. Empty plastic containers are recyclable or to be sent to recycling plants.

## INFINITY TECHNICAL TABLE

Aspect	dense liquid
Packaging	1l, 4l
Application tools	stainless steel trowel
Specific weight	1.100 ± 0.05 Kg/l
Theoretical yield	approx. 10-12m <sup>2</sup> /l per coat
Volumetric dry residue	35 ± 2%
Touch dry	4-5 hours at 20°C temperature
Dry to handle	12-18 hours at 20°C temperature
Dry to recoat	12 hours at 20°C temperature
VOC	10g/l wall paint and subcategory L max value UE2010: 30g/l
HS CODE	3209.90.00